



# LUMINES Lighting CLARO Linear LED Luminaire



**CLARO**  
by LUMINES<sup>®</sup>  
LIGHTING

LUMINES Lighting Linear LED Luminaire is dedicated mainly for indoor use. It is used as a main and decorative light source. Due to its minimalistic design, it allows for various interior arrangements.

Exact length of the luminaire [mm]	613
Fixture height [mm]	73
Fixture depth [mm]	43
Input voltage	220-240V AC
Useful luminous flux [lm] in a 120° cone	2680
Color temperature CCT [K]	4000
Color	White lacquered



## SET INCLUDES

LED luminaire	Aluminum
Light source	Samsung LED
Diffuser material	PMMA
Diffuser color	Milk
Set of suspensions	
Line	1250 mm x 1,2 mm
Line with a ball	100 mm
Cable lock	M4 9x29 nickel plated
Nipple	M10x1 nickel plated
Ceiling mounting bracket	15x15 M10x1 nickel


## PARAMETERS

Symbol	LUM-CLAROB-60-4K
Index	26-0000-02
Weight with packaging [kg]	2,15
Power on mode [W]	27
Energy efficiency class	E
Standby power [W]	0
Power factor	0,92
Total luminous flux [lm]	3270
Luminous efficiency [lm / W]	121,1
Peak light [cd / klm]	413,57
CRI Ra	>80
R9	11

Chromaticity Coordinates (x)	0,3827
Chromaticity Coordinates (y)	0,3800
Radiation angle (°)	100
Color uniformity in MacAdam ellipses	<4 degrees
Strobe Effect Indicator (SVM)	0,04
Flicker Index (Pst LM)	0,3
Lighting maintenance factor [%]	96
Dimmable	Not
IP	20
Lifespan L70B50	>54000
Guarantee	60 months



Power Factor <b>PF</b> ≥0,9	Voltage <b>220-240 V</b> 50-60 Hz	Power <b>27</b> W	CRI <b>Ra</b> >80	IP protection <b>IP20</b>	Beam angle <b>100°</b>	Lifespan <b>54 000 h</b>	off on <b>25 000</b>	60%	Starting time <b>&lt;0,02</b> s	Temperature range <b>+60</b> °C <b>-20</b>	
-----------------------------------	---	-------------------------	-------------------------	------------------------------	---------------------------	-----------------------------	-------------------------	-----	---------------------------------------	---	--




## How to install?



Scan the QR code to  
see the instructional video




# LUMINES Lighting CLARO Linear LED Luminaire



**CLARO**  
by **LUMINES**<sup>®</sup>  
LIGHTING

LUMINES Lighting Linear LED Luminaire is dedicated mainly for indoor use. It is used as a main and decorative light source. Due to its minimalistic design, it allows for various interior arrangements.

Exact length of the luminaire [mm]	1213
Fixture height [mm]	73
Fixture depth [mm]	43
Input voltage	220-240V AC
Useful luminous flux [lm] in a 120° cone	5400
Color temperature CCT [K]	4000
Color	White lacquered



## SET INCLUDES

LED luminaire	Aluminum
Light source	Samsung LED
Diffuser material	PMMA
Diffuser color	Milk
Set of suspensions	
Line	1250 mm x 1,2 mm
Line with a ball	100 mm
Cable lock	M4 9x29 nickel plated
Nipple	M10x1 nickel plated
Ceiling mounting bracket	15x15 M10x1 nickel


## PARAMETERS

Symbol	LUM-CLAROB-120-4K
Index	26-0000-00
Weight with packaging [kg]	3,24
Power on mode [W]	54
Energy efficiency class	E
Standby power [W]	0
Power factor	0,96
Total luminous flux [lm]	6640
Luminous efficiency [lm / W]	123
Peak light [cd / klm]	412,42
CRI Ra	>80
R9	11

Chromaticity Coordinates (x)	0,3827
Chromaticity Coordinates (y)	0,3800
Radiation angle (°)	100
Color uniformity in MacAdam ellipses	<4 degrees
Strobe Effect Indicator (SVM)	0,04
Flicker Index (Pst LM)	0,3
Lighting maintenance factor [%]	96
Dimmable	Not
IP	20
Lifespan L70B50	>54000
Guarantee	60 months



Power Factor <b>PF</b> ≥0,9	Voltage <b>220-240 V</b> 50-60 Hz	Power <b>54</b> W	CRI <b>Ra</b> >80	IP protection <b>IP20</b>	Beam angle <b>100°</b>	Lifespan <b>54 000 h</b>	off on <b>25 000</b>	60% <b>0,02 s</b>	Starting time <b>&lt;0,02</b> s	Temperature range <b>+60</b> °C <b>-20</b>	
-----------------------------------	---	-------------------------	-------------------------	------------------------------	---------------------------	-----------------------------	-------------------------	----------------------	---------------------------------------	---	--



## How to install?




Scan the QR code to  
see the instructional video






# LUMINES Lighting CLARO Linear LED Luminaire




**CLARO**  
by LUMINES<sup>®</sup>  
LIGHTING

LUMINES Lighting Linear LED Luminaire is dedicated mainly for indoor use. It is used as a main and decorative light source. Due to its minimalistic design, it allows for various interior arrangements.


Exact length of the luminaire [mm]	1813
Fixture height [mm]	73
Fixture depth [mm]	43
Input voltage	220-240V AC
Useful luminous flux [lm] in a 120° cone	8100
Color temperature CCT [K]	4000
Color	White lacquered

 **ENERG**<sup>+</sup>

LUMINES Lighting  
LUM-CLAROB-180-4K



**80**  
kWh/1000h



2019/2015

## SET INCLUDES

LED luminaire	Aluminum
Light source	Samsung LED
Diffuser material	PMMA
Diffuser color	Milk
Set of suspensions	
Line	1250 mm x 1,2 mm
Line with a ball	100 mm
Cable lock	M4 9x29 nickel plated
Nipple	M10x1 nickel plated
Ceiling mounting bracket	15x15 M10x1 nickel


## PARAMETERS

Symbol	LUM-CLAROB-180-4K
Index	26-0000-01
Weight with packaging [kg]	4,42
Power on mode [W]	80
Energy efficiency class	E
Standby power [W]	0
Power factor	0,98
Total luminous flux [lm]	9965
Luminous efficiency [lm / W]	124,3
Peak light [cd / klm]	412,42
CRI Ra	>80
R9	11

Chromaticity Coordinates (x)	0,3827
Chromaticity Coordinates (y)	0,3800
Radiation angle (°)	100
Color uniformity in MacAdam ellipses	<4 degrees
Strobe Effect Indicator (SVM)	0,04
Flicker Index (Pst LM)	0,3
Lighting maintenance factor [%]	96
Dimmable	Not
IP	20
Lifespan L70B50	>54000
Guarantee	60 months



Power Factor <b>PF</b> ≥0,9	Voltage <b>220-240 V</b> 50-60 Hz	Power <b>80</b> W	CRI <b>Ra</b> >80	IP protection <b>IP20</b>	Beam angle <b>100°</b>	Lifespan <b>54 000 h</b>	off on <b>25 000</b>	60% <b>0,02 s</b>	Starting time <b>&lt;0,02</b> s	Temperature range <b>+60</b> °C <b>-20</b>	
-----------------------------------	---	-------------------------	-------------------------	------------------------------	---------------------------	-----------------------------	-------------------------	----------------------	---------------------------------------	---	--



## How to install?



Scan the QR code to  
see the instructional video

